

## Specification

<b>Video</b>	
CCD Sensor	1/4" Sony Super HAD CCD
Total Pixels	PAL: 610K
H. Resolution	700TV Lines (750TV Lines in B/W)
Auto Iris Type	DC IRIS
Lens	3.4~122.4mm 36x Optical Zoom
Focus System	Automatic
S/N Ratio	More than 50dB (AGC Off)
M.Illumination	0Lux (with IR LED's On)
IR Distance	100 Metres in Ideal Conditions
Pan/Tilt	PAN 360°, Tilt -25°~205°
<b>OSD/DSP</b>	
Digital Zoom	OFF / 1x~32x
Day & Night	COLOUR / BW / AUTO (ICR)
BLC	ON / OFF
WDR	ON / OFF
Shutter Speed	AUTO / MANUAL (1/50~1/100000 sec)
White Balance	AUTO / ATW / INDOOR / OUTDOOR / ONEPUSH / MANUAL
Video Gain Control	0~15 Level
Noise Reduction	2D/3D (OFF/MANUAL / AUTO )
Privacy Zone	ON/OFF (8 Programmable Zones)
Presets	128 Programmable
Digital Flip	ON / OFF
Focus Control	AUTO / ZOOMMTG / MANUAL
Wipe	AUTO / PUSH / RUN
IR Angle	AUTO / 6°~60°
Motion Detection	ON / OFF
DIS	Yes
<b>Connectors/Switches/Mechanical</b>	
Video Out	BNCx1,1.0Vpp, 75Ω, Composite
Alarm Input	1
Alarm Ouput	1
RS485	Pelco D/P & other protocols
<b>Other</b>	
Environment	IP68
Power	AC24V 60W@Heater/Blower
Operating Temp.	-40°F~122°F
Dimension	200 x 469mm (Diameter x Height)
Weight	13.5Kg

Dimensions (mm)

